



UCM-30 SL BT



MAIN FEATURES

Interior dimensions (LxWxH)	450 x 400 x 220 (mm)
External dimensions (LxWxH)	500 x 450 x 920 (mm)
Useful measurements (LxWxH)	420 x 370 x 200 (mm)
Tank capacity	39 L
Ultrasonic power	400 W
Heating power	500 W
Ultrasound frequency	28/40 Khz

OTHER FEATURES

Tramex	Removable
Handles	Laterals
Platform Type	Manual
Maximum load	35 Kg
Opening/Closing Lid	Manual
Type of handle on lid	Ergonomic
Shock absorbers	Yes

TECHNOLOGY OF THIS EQUIPMENT

Integrated electrical panel

Patented generators

Replaceable ultrasounds

Submersible transmitter

Patented Technology

Optional small parts baskets

100% Spanish manufacturing and technology

Ultrasonic control with digital interface

Temperature control with digital interface

Safety button for emergency stop



It is recommended to maintain a distance of 100 to 150 mm between the workpiece and the tank walls for proper ultrasonic diffusion. Upon purchase of this ultrasonic cleaning machine, a user and maintenance manual will be provided, including detailed information about the equipment. The content of this document is for guidance only and does not establish any contractual commitment. It may be modified without prior notice to optimize the quality and service offered.